

AGRICULTURAL TRAILERS FOR TRANSPORTING CEREALS AND ANIMAL FEED



A.L.I. TC 60 AND CSR 140 AGRICULTURAL TRAILERS HAVE BEEN STUDIED AND DESIGNED IN EVERY DETAIL IN ORDER TO OBTAIN A STURDY AND LIGHT-WEIGHT MACHINE FOR TRANSPORTING AND UNLOADING CEREALS, GRAINS AND ANIMAL FEED.

FOR OVER 40 YEARS, THE CONTINUOUS AUGER UNLOADING SYSTEM, EQUIPPED WITH CARDAN JOINT AND OIL BATH REDUCER, HAS BEEN USED AND HIGHLY VALUED THANKS TO ITS QUALITIES OF SOLIDITY, ITS UNLOADING SPEED AND RELIABILITY IN EVERY SITUATION (EVEN THE MOST CRITICAL).

THE SELF-STEERING AXLE (WITH REALIGNMENT OF THE WHEELS IN REVERSE) FOR THE CSR 140 AND AN ACCURATE STUDY OF THE DISTRIBUTION OF MASSES ON THE TC 60 ALLOW TO GET EASY-TO-HANDLE TRAILERS, SUITABLE FOR USE IN ANY ENVIRONMENT.

TECHNICAL DATA OF TC / CSR TRAILERS

MODEL	TC 60/10	TC 60/13	TC 120	CSR 140
TRANSPORTED VOLUME	11,5 M ³	14 M ³	14 M ³	19,5 M ³
OVERALL DIMENSIONS (WIDTH X LENGTH X HEIGHT) CM	235x605x300	235x605x320	245x605x320	245x635x347
DEAD WEIGHT	1900 KG	1950 KG	3020 KG	3720 KG
APPROVED CAPACITY (ITALY)	60 q		120 q	140 q
UNLOADING HEIGHT WITH SWIVELING TUBE	7÷9 M			
HEIGHT OF THE VERTICAL UNLOADING TUBE	3,5 M		HYDRAULICALLY OPERATED SWIVEL AND UNLOADING TUBE	
AXLES	1		2	2 SELF-STEERING RE-AR AXLE
BRAKING SYSTEM	PNEUMATIC / HYDRAULIC			
STANDARD TYRES (8 HOLES)	385/65 R22.5		435/50 R	385/65 R22.5
UNLOADING SPEED	1,7 M ³ /MIN			

THE STANDARD SUPPLY OF THE TC TRAILER INCLUDES :

- VERTICAL UNLOADING
- HYDRAULIC SUPPORTING FOOT

THE STANDARD SUPPLY OF THE CSR TRAILER INCLUDES:

- SELF-STEERING AXLE
- BRAKE REGULATOR
- HYDRAULICALLY OPERATED SWIVEL AND UNLOADING TUBE



OPTIONS ON DEMAND:

- CRAMARO COVER/UNCOVER DEVICE
- HYDRAULIC SUPPORTING FOOT
- UNLOADING TO THE GROUND WITH HYDRAULIC OPENING
- DYNAMIC WEIGHING KIT (ONLY FOR TC TRAILERS)
- UNLOADING TUBE EXTENSIONS


ALI
 MECCANICA SRL

STRADA B N.10, Z.I. SAN ZENO, 52100, AREZZO, ITALIA

TEL. +39 0575 998446 FAX +39 0575 998447

EMAIL: INFO@ALIMECCANICA.COM

WWW.ALIMECCANICA.COM

